

1. Product and Company Identification

Product number 841
Product name Netcare Oil Base Stainless Steel Cleaner
Effective date 10-May-2011
Company information Network Services Company
 1100 East Woodfield Rd, Suite 200
 Schaumburg, IL 60173 United States
Company phone General Assistance 630-543-7600
Emergency telephone US 800-424-9300
Emergency telephone outside US 703-527-3887
Version # 03
Supersedes date 21-Apr-2011

2. Hazards Identification

Emergency overview Aerosol. FLAMMABLE
 CONTENTS UNDER PRESSURE.
 Irritating to eyes. Prolonged exposure may cause chronic effects.

Potential health effects

Routes of exposure Eye contact. Inhalation. Skin contact. Ingestion.

Eyes Contact may irritate or burn eyes. Eye contact may result in corneal injury.

Skin Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

Inhalation Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Prolonged inhalation may be harmful.

Ingestion Exposure by ingestion of an aerosol is unlikely. May cause delayed lung damage. Components of the product may be absorbed into the body by ingestion.

Target organs Central nervous system. Lungs.

Chronic effects Conjunctiva. May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion and blurred vision) and/or damage. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. May cause delayed lung injury.

Signs and symptoms Discomfort in the chest. Corneal damage. Narcosis. Coughing. Conjunctivitis. Defatting of the skin. Skin irritation.

3. Composition / Information on Ingredients

Components	CAS #	Percent
Paraffinic, Naphthenic Solvent	64742-47-8	20 - 30
Propane	74-98-6	15 - 20
Odorless Mineral Spirits	64742-48-9	10 - 15
Acetone	67-64-1	10 - 15
Methyl Acetate	79-20-9	8 - 10
Non-hazardous and other components below reportable levels		20 - 40

4. First Aid Measures
First aid procedures

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Skin contact Wash off with warm water and soap. Get medical attention if irritation develops and persists.

Inhalation	If symptoms develop move victim to fresh air. Oxygen or artificial respiration if needed. Call a physician if symptoms develop or persist.
Ingestion	If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not induce vomiting without advice from poison control center. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

5. Fire Fighting Measures

Flammable properties	Vapor or gas may spread to distant ignition sources and flash back. Runoff to sewer may cause fire or explosion hazard.
Extinguishing media	
Suitable extinguishing media	Water fog. Alcohol foam. Dry chemical. Carbon dioxide (CO2).
Protection of firefighters	
Specific hazards arising from the chemical	Fire may produce irritating, corrosive and/or toxic gases.
Protective equipment and precautions for firefighters	In case of fire and/or explosion do not breathe fumes. Containers should be cooled with water to prevent vapor pressure build up.

6. Accidental Release Measures

Methods for containment	Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Stop the flow of material, if this is without risk.
Methods for cleaning up	Should not be released into the environment. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

7. Handling and Storage

Handling	Pressurized container: Do not pierce or burn, even after use. Do not smoke while using or until sprayed surface is thoroughly dry. Use only in area provided with appropriate exhaust ventilation. Do not use if spray button is missing or defective. Do not re-use empty containers. Avoid contact with skin. Avoid prolonged exposure.
Storage	Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Keep away from heat and sources of ignition. Avoid exposure to long periods of sunlight. Store in cool place. Keep out of the reach of children. Keep away from food, drink and animal feedings. Level 3 Aerosol.

8. Exposure Controls / Personal Protection

Exposure limits

ACGIH

Components	CAS #	TWA	STEL	Ceiling
Propane	74-98-6	1000 ppm	Not established	Not established
Acetone	67-64-1	500 ppm	750 ppm	Not established
Methyl Acetate	79-20-9	200 ppm	250 ppm	Not established

OSHA

Components	CAS #	TWA	STEL	Ceiling
Propane	74-98-6	1000 ppm	Not established	Not established
Acetone	67-64-1	1000 ppm	Not established	Not established
Methyl Acetate	79-20-9	200 ppm	Not established	Not established

Personal protective equipment

Eye / face protection	Do not get in eyes. Chemical goggles are recommended.
Skin protection	Wear appropriate chemical resistant clothing. Chemical resistant gloves.
Respiratory protection	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

9. Physical & Chemical Properties

Appearance	Compressed liquefied gas.
Boiling point	365 °F (185 °C) estimated
Color	Colorless.
Density	0.7552 g/cm3 estimated
Flammability (HOC)	33.4869 kJ/g estimated
Flash back	No
Flash point	-156 °F (-104.4 °C) Propellant
Form	Aerosol.
Freezing point	Not available
Odor	solvent fruity
pH	Not Applicable
Physical state	Liquid.
Pressure	40 - 60 psig @ 70F
Solubility	Negligible
Specific gravity	0.7553 estimated

10. Chemical Stability & Reactivity Information

Chemical stability	Material is stable under normal conditions. Risk of ignition.
Conditions to avoid	Heat, flames and sparks.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological Information

Acute effects	Acute LC50: 24 mg/l/4h estimated, Rat, Inhalation
---------------	---

Component analysis - LD50

Toxicology Data - Selected LD50s and LC50s

Acetone	67-64-1	Oral LD50 Rat 5800 mg/kg
Methyl Acetate	79-20-9	Inhalation LC50 Rat 16000 ppm 4 h; Oral LD50 Rat >5000 mg/kg; Dermal LD50 Rat >2000 mg/kg; Dermal LD50 Rabbit >5000 mg/kg
Odorless Mineral Spirits	64742-48-9	Oral LD50 Rat >5000 mg/kg; Dermal LD50 Rabbit >3160 mg/kg
Paraffinic, Naphthenic Solvent	64742-47-8	Inhalation LC50 Rat >5.2 mg/L 4 h; Oral LD50 Rat >5000 mg/kg; Dermal LD50 Rabbit >2000 mg/kg
Propane	74-98-6	Inhalation LC50 Rat 658 mg/L 4 h

Sensitization	Not expected to be hazardous by OSHA criteria.
Teratogenicity	Not expected to be hazardous by OSHA criteria.

12. Ecological Information

Ecotoxicity	LC50 199 mg/L estimated, Fish, 96.00 Hours, EC50 10018 mg/L estimated, Daphnia, 48.00 Hours, IC50 1294 mg/L estimated, Algae, 72.00 Hours, Contains a substance which causes risk of hazardous effects to the environment.
-------------	---

13. Disposal Considerations

Waste codes	D001: Waste Flammable material with a flash point <140 F
Disposal instructions	Contents under pressure. Dispose of this material and its container to hazardous or special waste collection point. Do not incinerate sealed containers. If discarded, this product is considered a RCRA ignitable waste, D001.

14. Transport Information

Department of Transportation (DOT) Requirements

Basic shipping requirements:

Proper shipping name	Consumer commodity
Hazard class	ORM-D
Subsidiary hazard class	None
Additional information:	
Packaging exceptions	156, 306
Packaging non bulk	156, 306
Packaging bulk	None

IMDG

Basic shipping requirements:

Proper shipping name	AEROSOLS
Hazard class	2.1
UN number	1950
Additional information:	
Packaging exceptions	LTD QTY
Item	5F
Labels required	None
Transport Category	2



IATA

Basic shipping requirements:

Proper shipping name	Aerosols, flammable
Hazard class	2.1
UN number	1950
Additional information:	
Packaging exceptions	LTD QTY
Labels required	2.1



15. Regulatory Information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous chemical Yes

CERCLA (Superfund) reportable quantity

Acetone: 5000.0000

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 302 extremely hazardous substance	No
Section 311 hazardous chemical	Yes
Hazard categories (311/312)	Immediate Hazard - Yes Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of New and Existing Chemicals (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations**U.S. - Pennsylvania - RTK (Right to Know) List**

Acetone	67-64-1	Environmental hazard
Methyl Acetate	79-20-9	Present
Odorless Mineral Spirits	64742-48-9	Present
Paraffinic, Naphthenic Solvent	64742-47-8	Present
Propane	74-98-6	Present

16. Other Information**Further information**

HMIS® is a registered trade and service mark of the NPCA.

HMIS® ratings

Health: 1*

Flammability: 4

Physical hazard: 0

Personal protection:

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

MSDS sections updated

Product and Company Identification: Product and Company Identification

Composition / Information on Ingredients: Ingredients

Physical & Chemical Properties: Physical & Chemical Properties

Prepared by

Regulatory Compliance