

MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

IDENTITY AND DISTRIBUTOR'S INFORMATION						
NFPA Rating: Health-1; Flammability-3; Reactivity-0; Special- -			HMIS Rating: Health-1; Flammability-3; Reactivity-0; Personal Protection-B			
Manufactured For: WAXIE Sanitary Supply			DOT Hazard Classification: ORM-D			
Address: 9353 Waxie Way			Identity (trade name as used on label):			
Address: San Diego, CA 92193-1036			Slip Shot Multi-Purpose Red Grease			
Phone: 1-800-995-4466			MSDS Number: A00727 Revision- 10			
Emergency Response Number: 1-800-255-3924			Date Prepared: 06/06/03 Prepared By: AH/IB			
NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA Information Calls: 858-292-8111						
SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION						
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES (Hazardous Components 1% or greater; Carcinogens 0.1% or greater)		CAS Number	SARA III LIST	OSHA PEL (ppm)	ACGIH TLV (ppm)	Carcinogen Ref. Source **
PETROLEUM DISTILLATE		8002-05-9	No	500	500	d
ISOBUTANE		75-28-5	No	800	800	d
PROPANE		74-98-6	No	1000	1000	d
HEPTANE		142-82-5	No	500	500	d
ACETONE		67-64-1	No	1000	750	d
PARAFFINIC PETROLEUM DISTILLATE		64742-47-8	No	100	N/E	d
SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS						
Boiling Point: N/A			Specific Gravity (H2O=1): Concentrate Only = .81			
Vapor Pressure: PSIG @ 70°F (Aerosols): 25-46 psig			Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A			
Vapor Density (Air = 1): ND			Evaporation Rate (= 1): N/E			
Solubility in Water: Nil			Water Reactive: No			
Appearance and Odor: Red color with solvent odor.						
SECTION 3 - FIRE AND EXPLOSION HAZARD DATA						
FLAMMABILITY as per USA FLAME PROJECTION TEST (aerosols) >18" w/flash back to tip: EXTREMELY FLAMMABLE		Auto Ignition Temperature	Flammability Limits in Air by % in Volume:			
		N/E	% LEL: N/E	% UEL: N/E		
FLASH POINT AND METHOD USED (non-aerosols): N/A		SPECIAL FIRE FIGHTING PROCEDURES: Use water fog to cool containers to prevent rupturing and bursting.				
EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide.						
Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture. Provide shielding to protect personnel.						
SECTION 4 - REACTIVITY HAZARD DATA						
STABILITY [X] STABLE [] UNSTABLE		HAZARDOUS POLYMERIZATION [] WILL [X] WILL NOT OCCUR				
Incompatibility (Mat. to avoid): Oxygen & oxidants.		Conditions to Avoid: Open flame, welding arcs, heat, sparks.				
Hazardous Decomposition Products: Carbon dioxide, carbon monoxide.						
SECTION 5 - HEALTH HAZARD DATA						
PRIMARY ROUTES OF ENTRY: [X] INHALATION [] INGESTION [] SKIN ABSORPTION [X] EYE [] NOT HAZARDOUS						
ACUTE EFFECTS						
Inhalation: Can cause headaches, dizziness.						
Eye Contact: Irritation			Skin Contact: Can cause skin defatting.			
Ingestion: Possible chemical pneumonitis if aspirated into lungs.						
CHRONIC EFFECTS: None known.						
Medical Conditions Generally Aggravated by Exposure: Asthma.						
EMERGENCY FIRST AID PROCEDURES						
Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention.						
Skin Contact: Wash with soap and water. If irritated, seek medical attention.						
Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.						
Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.						
SECTION 6 - CONTROL AND PROTECTIVE MEASURES						
Respiratory Protection (specify type): Not normally needed. If TLV is exceeded, use respirator approved by NIOSH for organic vapors.						
Protective Gloves: Solvent resistant.			Eye Protection: Safety glasses.			
Ventilation Requirements: Normal room ventilation is sufficient with periodic use. For continuous spray, local exhaust provided by explosion proof motor is recommended.						
Other Protective Clothing & Equipment: None required. Eyewash station suggested.						
Hygienic Work Practices: Wash with soap and water after contact.						
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE						
Steps To Be Taken If Material Is Spilled Or Released: Cover with absorbent material and sweep up. Wash area to prevent slipping. Incinerate or landfill according to local, state or federal regulations.						
Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.						
Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F.						
Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN.						

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

** Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data O